

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE WEST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 6 AND 7,

IN

TOWNSHIP 32 SOUTH, RANGE 7 WEST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Jeremy D. Davis
Cadastral Surveyor

Under special reassignment instructions dated *June 1, 2009*, approved *June 1, 2009*, which provided for the surveys included under Group Number *1084*, and assignment instructions dated *June 1, 2009*.

Survey Commenced, *June 2, 2009*
Survey Completed, *June 24, 2009*

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE WEST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 6 AND 7,

IN

TOWNSHIP 32 SOUTH, RANGE 7 WEST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Jeremy D. Davis
Cadastral Surveyor

Under special reassignment instructions dated *June 1, 2009*, approved *June 1, 2009*, which provided for the surveys included under Group Number *1084*, and assignment instructions dated *June 1, 2009*.

Survey Commenced, *June 2, 2009*
Survey Completed, *June 24, 2009*

INDEX DIAGRAM

Township 32 South, Range 7 West.

4 6 13	14 5 5 13	4	3	2	1
3 7 11	11 8 4 10	9	10	11	12
18 8	9 17	16	15	14	13
19 6	8 20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

The Subdivision of Section 6.....14
The Subdivision of Section 7.....16

TOWNSHIP 32 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

The following field notes are those of the dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines, and the subdivision of sections 6 and 7, in Township 32 South, Range 7 West, Salt Lake Meridian, Utah.

History of Surveys

Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY			
Portion	J. Gorlinski	1871	
All	A.J. Stewart Jr.	1873	A.J. Stewart Jr. 1873
All			J.R. & Q. Stewart 1910
EAST BOUNDARY			
All	A.J. Stewart Jr.	1873	
All			J.R. & Q. Stewart 1910
Portion			L.V. Judd 2004
WEST BOUNDARY			
All	J. Gorlinski	1871	
Portion			T.C. Bailey 1881
Portion			J.R & Q. Stewart 1910
Remonumentation			F.D. Reynolds 1970
All			L.V. Judd 1997-98
NORTH BOUNDARY			
Portion	J. Gorlinski	1871	
Portion	J.R. & Q. Stewart	1910	J.R. & Q. Stewart 1910
Portion			L.V. Judd 2004
Portion			C.S. Bishop 2005-06
SUBDIVISION			
Portion	J. Gorlinski	1871	
Portion	J.R. & Q. Stewart	1910	J.R. & Q. Stewart 1910
Portion			L.V. Judd 2004

TOWNSHIP 32 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

This survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1084, dated June 1, 2009.

The direction of the lines were determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards and Guidelines for Cadastral Surveys Using GPS Methods*, dated May 9, 2001, Version 1.0. Trimble model 5800 GPS receivers were used for field collection. Cadastral Measurement Management (CMM) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and their calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic Control was derived from GPS static observations, post processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): DELTAAMUNI_UT2004 CORS ARP, FREDONIA CORS ARP, CITY OF PAGE CORS ARP.

The geographic position of the corner of sections 19, 20, 29, and 30, as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: 37°59'58.795" N. Longitude: 112°40'54.565" W.
N.A.D. 1983, Network Accuracy = 0.200 meter at 95% confidence.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
TOWNSHIP 32 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Dependent Resurvey of a Portion of the West Boundary,
T. 32 S., R. 7 W., Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by J. Gorlinski in 1871,
and the Resurveys Executed by T.C. Bailey in 1881, and L.V. Judd
in 1998.

Beginning at the corner of sections 7, 12, 13, and 18, monumented
with an aluminum post, 2 1/2 inches diameter, firmly set,
projecting 5 inches above the ground, with aluminum cap marked as
described in the official record of the 1998 resurvey.

Corner falls in a fence line extending north and south.

N. 0°18.5' W., between sections 7 and 12.

- 20.143 The S 1/16 section corner of sections 7 and 12, monumented with an
aluminum post, 2 1/2 inches diameter, firmly set, projecting 3
inches above the ground, with aluminum cap marked as described in
the official record of the 1998 resurvey.

Corner falls on north side of the intersection of fences extending
east and south.

N. 0°18.8' W., beginning new measurement.

- 20.151 Point for the 1/4 section corner of sections 7 and 12, at
proportionate distance; there is no remaining evidence of the
original corner.

Corner point falls within cultivated land unsuitable for permanent
monumentation, not monumented.

- 39.780 The witness point of sections 7 and 12, monumented with an
aluminum post, 2 1/2 inches diameter, set flush with ground, with
aluminum cap marked as described in the official record of the
1998 resurvey.

Corner falls at the east edge of a cultivated field, and on the
west edge of a road.

N. 0°18.8' W., beginning new measurement.

- 20.667 Point for the corner of sections 1, 6, 7, and 12, at proportionate
distance; there is no remaining evidence of the original corner.

Corner point falls within cultivated land unsuitable for permanent
monumentation, not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
TOWNSHIP 32 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

N. 0°18.8' W., between sections 1 and 6.

- 20.145 The S 1/16 section corner of sections 1 and 6, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 3 inches above the ground, with aluminum cap marked as described in the official record of the 1998 resurvey.

Found a steel fence post alongside the aluminum post.

Corner falls on level ground, 15 ft. north of the intersection of fences extending north and east.

N. 0°18.7' W., beginning new measurement.

- 20.145 The 1/4 section corner of sections 1 and 6, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, flush with ground, with aluminum cap marked as described in the official record of the 1998 resurvey.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 7 W., Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by J. Gorlinski in 1871,
and the Resurvey Executed by J.R. and Q. Stewart in 1910.

From the corner of sections 8, 9, 16, and 17, monumented with an iron post, not of record, 2 inches diameter, firmly set, in a scattered mound of stone, projecting 18 inches above the ground, with brass cap marked:

T32SR7W

S8	S9
S16	S17

 1910

Found marked stone lying loose alongside the iron post, marked with 4 notches on two edges. This monument is accepted as a careful and faithful establishment of the corner position.

No remaining evidence of the original bearing tree was found.

Rebuild mound of stone, 2 ft. base, to top of brass cap.

Set a steel fence post alongside the iron post.

Corner falls on a gradual southwest slope in piñon and juniper growth.

N. 0°06.5' E., between sections 8 and 9.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 32 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

- 41.477 The 1/4 section corner of sections 8 and 9, monumented with an iron post, not of record, 1 inch diameter, firmly set, in a mound of stone, with brass cap marked:

1/4
S8 | S9
1910

Found marked stone lying loose alongside the iron post, marked 1/4 on face. This monument is accepted as a careful and faithful establishment of the corner position.

Rebuild mound of stone, 3 ft. base, to top of brass cap.

Set a steel fence post northeast of the iron post.

Corner falls on a gradual southwest slope in piñon and juniper growth.

N. 0°09.2' E., beginning new measurement.

- 38.538 The corner of sections 4, 5, 8, and 9, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone 3 ft. base, to top of brass cap marked as described in the official record of the 1910 resurvey.

from which the remaining 1910 bearing tree

A piñon, down and dead, scribed T32S R7W S8 BT, on an open blaze, not remeasured.

Corner falls on a gradual northwest slope in piñon and juniper growth.

Reestablishment of the Survey Executed
by J. Gorlinski in 1871.

N. 1°39.3' W., between sections 4 and 5.

- 43.191 The 1/4 section corner of sections 4 and 5, monumented with a lava stone, 15x12x10 inches, firmly set, dimly marked 1/4 on west face, witnessed with a small mound of stone to the east. (Record; limestone)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 32 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T32SR7W
1/4
S5 | S4
2009

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Raise a small mound of stone, west of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in sagebrush and scattering juniper growth.

N. 1°08.2 W., beginning new measurement.

41.338 The corner of sections 4, 5, 32, and 33, on the north boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 4 inches above the ground, with aluminum cap marked as described in the official record of the 2006 resurvey.

Found a steel fence post alongside the aluminum post.

Found a mound of stone, 3 ft. base, 2 ft. high, north of the aluminum post.

Corner falls on flat ground in sagebrush.

Reestablishment of the Survey Executed by J. Gorlinski in 1871,
and the Resurvey Executed by J.R. and Q. Stewart in 1910.

From the corner of sections 19, 20, 29, and 30, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, 3 ft. base, with brass cap incorrectly marked:

T32SR7W
S19 | S24
S30 | S25
1910

I remark the brass cap as described in the official record of the 1910 resurvey.

from which the original bearing trees

A piñon, down and dead, with visible scribe marks on an open blaze, not remeasured.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
 CHAINS TOWNSHIP 32 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

A juniper, 10 inches diameter, bears N. 30° W., 28 links distance, with visible scribe marks on a partially healed blaze.

Corner falls on a gradual northwest slope in piñon and juniper growth.

N. 89°41.3' W., between sections 19 and 30.

40.408 The 1/4 section corner of sections 19 and 30, monumented with a lava stone, 18x11x5 inches, firmly set, marked 1/4 on north face, witnessed with a mound of stone to the north. (Record; white sandstone)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T32SR7W
 S19
 1/4 —
 S30
 2009

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Raise a mound of stone, 2 ft. base, 2 ft. high, north of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat open ground.

N. 89°59.6' W., beginning new measurement.

40.254 The corner of sections 19, 24, 25, and 30, on the west boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 3 inches above the ground, with aluminum cap marked as described in the official record of the 1998 resurvey.

Corner falls 2 ft. north of the intersection of fences extending north and west.

Reestablishment of the Survey Executed by J. Gorlinski
 in 1871.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 32 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

From the corner of sections 19, 20, 29, and 30.

N. 0°29.8' W., between sections 19 and 20.

- 39.971 Point for the 1/4 section corner of sections 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to solid rock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T32SR7W
1/4
S19 | S20
2009

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on a gradual south slope, between two large conglomerate rock outcroppings, in scattering piñon and juniper growth.

- 79.942 The corner of sections 17, 18, 19, and 20, monumented with a surface lava stone, 24x18x6 inches, firmly set, marked 5 grooves on east face, and no discernable marks on south edge or face. (Record; surface iron rock, 28x20x12)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground to solid rock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T32SR7W
S18 | S17
S19 | S20
2009

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in piñon and juniper growth.

N. 89°59.7' W., between sections 18 and 19.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 32 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

- 40.141** The 1/4 section corner of sections 18 and 19, monumented with a grey sandstone, 12x11x8 inches, firmly set, marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked:

T32SR7W
S18
1/4 ———
S19
2009

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Raise a mound of stone, 3 ft. base, 1 ft. high, north of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in sagebrush.

N. 88°41.0' W., beginning new measurement.

- 40.236** The corner of sections 13, 18, 19, and 24, on the west boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, flush with ground, with aluminum cap marked as described in the official record of the 1998 resurvey.

Found a steel fence post alongside the aluminum post.

Found a small mound of stone west of the aluminum post.

Corner falls on line of a fence extending north and south.

From the corner of sections 17, 18, 19, and 20.

N. 0°06.1' W., between sections 17 and 18.

- 41.149** The 1/4 section corner of sections 17 and 18, monumented with a white sandstone, 15x9x6 inches, firmly set, marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground to solid rock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 32 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T32SR7W
1/4
S18 | S17
2009

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls in a draw, bears north and south, in scattering piñon and juniper growth.

N. 0°47.9' W., beginning new measurement.

- 40.640 The corner of sections 7, 8, 17, and 18, monumented with a grey sandstone, 11x7x7 inches, firmly set, in a small mound of stone, marked 5 notches on east, and 4 notches on south edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, in a mound of stone, 2 ft. base, to top of aluminum cap marked:

T32SR7W
S7 | S8
S18 | S17
2009

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in sagebrush.

From the corner of sections 8, 9, 16, and 17.

N. 87°33.4' W., between sections 8 and 17.

- 40.611 The 1/4 section corner of sections 8 and 17, monumented with a grey sandstone, 14x12x9 inches, firmly set, marked 1/4 on north face.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 32 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T32SR7W
S8
1/4 —
S17
2009

Deposit the marked stone alongside the aluminum post.

Deposit a steel sign at the base of the aluminum post as a memorial.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in piñon and juniper growth.

N. 88°49.7' W., beginning new measurement.

40.953 The corner of sections 7, 8, 17, and 18.

S. 89°51.3' W., between sections 7 and 18.

40.010 Point for the 1/4 section corner of sections 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T32SR7W
S7
1/4 —
S18
2009

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Raise a small mound of stone north of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in sagebrush.

80.120 The corner of sections 7, 12, 13, and 18, on the west boundary of the township, hereinbefore described.

From the corner of sections 7, 8, 17, and 18.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 32 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

N. 0°14.5' E., between sections 7 and 8.

- 40.308 The 1/4 section corner of sections 7 and 8, monumented with a trachyte stone, 12x8x3 inches, firmly set, marked 1/4 on west face, witnessed with a mound of stone, 2 ft. base, to the west. (Record; grey sandstone, 12x10x8)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T32WR7W
1/4
S7 | S8
2009

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Raise a small mound of stone west of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in sagebrush.

N. 0°03.4' W., beginning new measurement.

- 40.340 The corner of sections 5, 6, 7, and 8, monumented with a lava rock, 18x10x6 inches, firmly set, in a small mound of stone, marked 5 notches on east and south edges. (Record; conglomerate, 14x10x8)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T32SR7W
S6 | S5
S7 | S8
2009

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Raise a mound of stone, 2 ft. base, 2 ft. high, west of the aluminum post.

Set a steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 32 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Corner falls on flat ground in sagebrush.

From the corner of sections 4, 5, 8, and 9.

N. 88°00.5' W., between sections 5 and 8.

- 42.327 The 1/4 section corner of sections 5 and 8, monumented with a brown lava stone, 12x8x7 inches, firmly set, marked 1/4 on north face. (Record; white sandstone, 14x10x8)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T32SR7W
S5
1/4 —
S8
2009

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in sagebrush.

N. 87°28.5' W., beginning new measurement.

- 39.290 The corner of sections 5, 6, 7, and 8.
-

S. 89°48.8' W., between sections 6 and 7.

- 40.336 Point for the 1/4 section corner of sections 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T32SR7W
S6
1/4 —
S7
2009

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 32 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.
CHAINS

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls 6.9 ft. east of a fence extending north and south.

80.672 Point for the corner of sections 1, 6, 7, and 12, on the west boundary of the township, hereinbefore described.

From the corner of sections 5, 6, 7, and 8.

N. 0°28.5' W., between sections 5 and 6.

40.230 The 1/4 section corner of sections 5 and 6, monumented with a lava stone, 14x11x8 inches, firmly set, marked 1/4 on west face. (Record; grey sandstone, 13x10x8)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked:

T32SR7W
1/4
S6|S5
2009

Deposit the marked stone alongside the aluminum post.

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat open ground.

N. 0°24.7' W., beginning new measurement.

40.427 The corner of sections 5, 6, 31, and 32, on the north boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, in a mound of stone, 2 ft. base, to top of aluminum cap marked as described in the official record of the 2006 resurvey.

Found a steel fence post alongside the aluminum post.

Corner falls on flat open ground.

The Subdivision of Section 6,
T. 32 S., R. 7 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 6 and 7.

THE SUBDIVISIONAL OF SECTION 6,
TOWNSHIP 32 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

N. $0^{\circ}21.0'$ W., on the N-S centerline of section 6.

20.130 Point for the center S 1/16 section corner of section 6.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

C
S1/16 | S6
C
2009

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls S. 30° E., 12.2 ft., from the intersection of fences extending south and west, and 5 ft. east of a fence extending north and south.

40.260 Point for the center 1/4 section corner, at intersection with the E-W centerline of section 6.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T32SR7W
C 1/4
S6
2009

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground in sagebrush.

80.639 The 1/4 section corner of sections 6 and 31, on the north boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, flush with ground, with aluminum cap marked as described in the official record of the 2006 resurvey.

Found a steel fence post alongside the aluminum post.

Corner falls on flat open ground, underneath high voltage power lines extending northeast and southwest.

From the 1/4 section corner of sections 5 and 6.

S. $89^{\circ}51.4'$ W., on the E-W centerline of section 6.

40.247 The center 1/4 section corner of section 6.

THE SUBDIVISIONAL OF SECTION 6,
TOWNSHIP 32 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

80.553 The 1/4 section corner of sections 1 and 6, on the west boundary of the township, hereinbefore described.

From the center S 1/16 section corner of section 6.

S. 89°50.1' W., on the E-W centerline of the SW 1/4 of section 6.

40.323 The S 1/16 section corner of sections 1 and 6, on the west boundary of the township, hereinbefore described.

The Subdivision of Section 7,
T. 32 S., R. 7 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 7 and 18.

N. 0°08.7' W., on the N-S centerline of section 7.

20.150 Point for the center S 1/16 section corner of section 7.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

C
S 1/16 | S7
C
2009

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner falls on flat ground, 2.8 ft. east of a fence extending north and south.

40.300 Point for the center 1/4 section corner, at intersection with the E-W centerline of section 7.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T32SR7W
C 1/4
S7
2009

Deposit a magnet enclosed in a plastic case at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

THE SUBDIVISIONAL OF SECTION 7,
TOWNSHIP 32 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Corner falls on flat ground, 5 ft. east of a fence extending north and south.

80.618 The 1/4 section corner of sections 6 and 7.

From the 1/4 section corner of sections 7 and 8.

S. 89°50.7' W., on the E-W centerline of section 7.

40.279 The center 1/4 section corner of section 7.

80.502 Point for the 1/4 section corner of sections 7 and 12, on the west boundary of the township, hereinbefore described.

From the center S 1/16 section corner of section 7.

S. 89°50.7' W., on the E-W centerline of the SW 1/4 of section 7.

40.166 The S 1/16 section corner of sections 7 and 12, on the west boundary of the township, hereinbefore described.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS


Name	Capacity
Vincent Porter	Survey Aide

CERTIFICATE OF SURVEY

I, *Jeremy D. Davis*, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of the *1st day of June, 2009*, I have *dependently resurveyed a portion of the west boundary, and a portion of the subdivisional lines, and subdivided sections 6 and 7, in Township 32 South, Range 7 West*, of the *Salt Lake* Meridian, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

6/28/10

Date



(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the west boundary, and a portion of the subdivisional lines, and subdivided sections 6 and 7, in Township 32 South, Range 7 West, Salt Lake Meridian, Utah*, executed by *Jeremy D. Davis, Cadastral Surveyor*, having been critically examined and found correct, are hereby approved.

December 1, 2010

Date



(Chief Cadastral Surveyor for Utah)